



Renewable Lubricants, Inc.

Distributed By: DM's Bio-Based Fluid Supply Inc.
10 McEwan Dr. W, Unit 4B
Bolton, ON, Canada L7E 1H1
Voice: 905.951.1100 Fax: 905.951.2100
www.dmsbiobased.ca

Bio-Synthetic™ 80W90 GL-5 Gear Lubricant



"Bio-based Lubricants that Perform Like Synthetics"

Bio-Synthetic™ 80W90 GL-5 is designed to meet the SAE J306 requirements for manual transmissions, differentials, and heavy equipment transfer cases. Increasing the GL-5 additive technology provides additional performance and Extreme Pressure (EP) protection for spiral bevel and hypoid gears. This biobased formula has combined Stabilized HOBS technology with synthetic base stocks to provide a super high viscosity index (VI) with fuel savings performance. The result is an inherently biodegradable product which has the long life heat stability but which additionally offers the protection advantages of increased gear life through extremely high film strength and excellent low temperature performance. This product may be used for top-off of differentials and is compatible with hydrocarbon and synthetic PAO based gear oils. Bio-Synthetic™ 80W90 GL-5 Gear Lubricant is an ENVIRONMENTALLY RESPONSIBLE lubricant that is formulated from renewable agricultural resources. We believe Earth's environmental future rests in the use of renewable material.

Typical Specifications

SAE Gear Grade	80W90
Specific Gravity @60°F (D-287)	0.92
VISCOSITIES:	
@100°C., cSt. (D-445)	18.4
@40°C., cSt. (D-445)	111
Viscosity Index (D-2270)	185
Viscosity, Brookfield cP @ -26°C	90,000
Flash Point, COC, °C (D-92)	260
Pour Point, °C (D-97)	-36
Copper Corrosion Strip 3hr @ 100°C (D-130)	1B
4 Ball Wear, 1h, 167°F, 1200 RPM, 40kg (D-4172)	.30
FZG Test (DIN 51517)	>12
Demulsibility (D-2711)	Pass
Foam Sequence I, II, III (D-892)	Pass
Rust Prevention (D-665 A&B)	Pass

Features

- (1) Recommended for API Service Classifications GL-3, GL-4, GL-5, MT-1, and GL-6
- (2) Super high viscosity index and low pour point for wide temperature usage
- (3) Fortified with additives to resist wear, oxidation, rust and foam
 - (4) Exceeds U.S. Steel and AGMA antiwear and EP performance for industrial applications
 - (5) Excellent low temperature channeling and demulsibility properties
 - (6) Biodegradable and Energy Conserving

STABILIZED by Renewable Lubricants* is RLI's trademark on their proprietary and patented anti-oxidant, anti-wear, and cold flow technology. High Oleic Base Stock (HOBS) are agricultural vegetable oils. This Stabilized technology allows the HOBS to perform as a high performance formula in high and low temperature applications, reducing oil thickening and deposits.

Patented Product: US Patent 6,383,992, US Patent 6,534,454 with additional Pending and Foreign Patents

* Trademark of Renewable Lubricants, Inc.
Copyright 1999 Renewable Lubricants, Inc.

Availability **F.O.B. :Bolton, ON, Canada**

5 Gallon Pails **Drums** **Bulk**