



Renewable Lubricants, Inc.

Distributed By: DM's Bio-Based Fluid Supply Inc.
 10 McEwan Dr. W, Unit 4B
 Bolton, ON, Canada L7E 1H1
 Voice: 905.951.1100 Fax: 905.951.2100
www.dmsbiobased.ca

Bio-Food Grade™ E.P. Grease **NLGI # 0, # 1, #2 (High Temperature)**



"Bio-based Lubricants that Perform Like Synthetics"

Bio-Food Grade™¹ E.P. Greases are high temperature Bio-based greases with excellent E.P. and Antiwear performance. The super high viscosity index of the Stabilized* HOBS naturally improves the thermal shear stability and load capacity. They were engineered specifically for food processing and packaging machinery. Bio-Food Grade™ E.P. Greases are rust and oxidation inhibited formulas that are very resistant to water and maybe used as open or enclosed gear greases. These products provide superior high temperature performance and good adhesion/cohesion properties. They have a neutral odor and are non-staining. The # 1 & # 0 are Supreme High Temperature Food Grade Grease with improved cold temperature mobility over Bio-Food Grade™ E.P. NLGI #2. Bio Food Grade™ E.P. Grease contains an optimized blend of preservatives. The preservatives exhibit broad spectrum antimicrobial activity against Gram positive and Gram negative bacteria, yeasts and mold.

NSF Registration:	NLGI # 1 140452 H1	NLGI # 0 140451 H1	NLGI # 2 140453 H1
Typical Specifications:			
Base Oil -Viscosity @ 40°C cSt ASTM D 445	42.10	42.10	42.10
Viscosity @ 100°C cSt ASTM D 445	8.69	8.69	8.69
Viscosity Index ASTM D 2270	191	191	191
Pour Point ASTM D 97	-30°C	-30°C	-30°C
Color	White	White	White
Thickener	Alum Complex	Alum Complex	Alum Complex
Drop Point ASTM D 566	500° F (260° C)	NA	520° F (271° C)
Water Washout @ 79° C ASTM D 1264	3.4 % Loss	NA	2.0% Loss
Mobility Test-US Steel Method			
40°C			113.00 g/min
0°C			16.98 g/min
-20°C			1.15g/min
4-Ball Wear ASTM D 2266	0.46 mm	0.46 mm	0.43 mm
4-Ball EP ASTM D 2596	Weld 250	Weld 250	Weld 250
Timken OK Load ASTM D 2509.	40 lbs.	40 lbs.	40 lbs.
Pen, Unwkd ASTM D 217	325 mm/10	380 mm/10	286 mm/10
Pen, Wkd 60 ASTM D 217	320 mm/10	390 mm/10	295 mm/10
Pen, Wkd 10,000	340 mm/10	390 mm/10	304 mm/10
Pen, Wkd 100,000	340 mm/10	390 mm/10	293 mm/10
ASTM D 217 strokes change from 60 strokes			
Roll Stability ASTM D 1831	-3.5%	385%	+3.6%
Cone Bleed @ 100° C ASTM D 6184	3.7 % Loss	NA	2.2 % Loss
Copper Corrosion ASTM D 130	1A	1A	1A
Oil Separation ASTM D 1742	4.6 % Loss	NA	1.1 % Loss
Rust Test ASTM D 1743	Pass	Pass	Pass
Bomb Oxidation, 100 h. ASTM D 942	5.0 psi	5.0 psi	5.0 psi

STABILIZED by Renewable Lubricants* is RLI's trademark on their proprietary and patented technology. High Oleic Base Stock (HOBS) are agricultural vegetable oils. This Stabilized technology allows the HOBS to perform as a high performance formula in high and low temperature applications, reducing oil thickening and deposits.

¹This product is acceptable as a lubricant with incidental food contact (H1) for use in and around food processing areas. Such compounds may be used on food processing equipment as a protective anti-rust film, as a release agent on gaskets or seals of tank closures, and as a lubricant for machine parts and equipment in locations in which there is a potential exposure of the lubricated part to food.

Patented Product with Pending and Foreign Patents

* Trademark of Renewable Lubricants, Inc.
 Copyright 1999 Renewable Lubricants, Inc.

Availability **F.O.B. :Bolton, ON, Canada** **14 oz. Tubes** **35 lb Pails** **120 lb Kegs** **400 lb Drums**