



## Renewable Lubricants, Inc.

Distributed By: DM's Bio-Based Fluid Supply Inc.  
10 McEwan Dr. W, Unit 4B  
Bolton, ON, Canada L7E 1H1  
Voice: 905.951.1100 Fax: 905.951.2100  
[www.dmsbiobased.ca](http://www.dmsbiobased.ca)



### **Bio-Parts Cleaner/Degreaser™** **(Soy Based and Food Grade<sup>1</sup> H1)**

#### *"Bio-based Lubricants that Perform Like Synthetics"*

A specially formulated, <sup>1</sup>ultimately biodegradable Soy Cleaner/Degreaser that is a safe improvement over petroleum solvents for cleaning parts and equipment in food processing plants. This safe, nonflammable bio-based product contains no hazardous Volatile Organic Compounds (VOCs), and has been formulated with anti-oxidants for improved stability. It provides a direct replacement for mineral spirits and stoddard solvents (excellent electrical insulating value @ 47KV). This all-purpose product removes oily grimy dirt on used parts for maintenance and repairs and is excellent for cleaning engines, transmissions, differentials, electric motors, and machinery parts before rebuilding. Exceptional for cleaning road grime, pine sap, and tar on vehicles. EPA, OSHA, Workers Acceptance is high with Bio-based Products.

Applications for: –Food Manufacturing –Military –Industrial –Transportation –Marine –Agricultural –Mining

Non-flammable cleaning of: Jacks, Bearings, Bolts, Linkage Cables, Dies,

Wire Ropes, Chains, Tracks, Slides, Shafts, Assembly Parts, Hand Tools, Power Tools,

Firearms, Air Tools, Machine Tools, etc.

#### **TYPICAL TEST DATA:**

ASTM D-445 3.9 cSt @ 40°C

ASTM D-97 Pour Point -2°C

Pound Per Gallon 7.16

ASTM D-877 Dielectric Strength >40KV

ASTM D-92 Flash Point 149 °C

ASTM D-665 A Corrosion Test Pass

ASTM D-130 Copper Corrosion 1a

Emulsification with Water- None

<sup>1</sup> Base oils and additives in this product are listed in 21 CFR 178.3570, Lubricants for incidental food contact (USDA H-1). Full compliance with other applicable restrictions of FDA, USDA, oil spill, and oil pollution prevention statutes is recommended.

STABILIZED by Renewable Lubricants\* is RLI's trademark on their proprietary and patented anti-oxidant, anti-wear, and cold flow technology. High Oleic Base Stock (HOBS) are agricultural vegetable oils. This Stabilized technology allows the HOBS to perform as a high performance formula in high and low temperature applications, reducing oil thickening and deposits.

<sup>1</sup> Ultimate Biodegradation (Pw1) within 28 days in ASTM D-5864 Aerobic Aquatic Biodegradation of Lubricants

Proprietary Formula

\* Trademark of Renewable Lubricants, Inc.

Copyright 2002 Renewable Lubricants, Inc.

**Availability**

**F.O.B. :Bolton, ON, Canada**

**1 Gallon**

**5 Gallon Pails**

**Drums**

**Bulk**