



Renewable Lubricants, Inc.

Distributed By: DM's Bio-Based Fluid Supply Inc.
 10 McEwan Dr. W, Unit 4B
 Bolton, ON, Canada L7E 1H1
 Voice: 905.951.1100 Fax: 905.951.2100
www.dmsbiobased.ca

Bio-AW Turbine™ R & O Fluids **(ISO 32, 46, 68, 100)**



"Bio-based Lubricants that Perform Like Synthetics"

Bio-AW Turbine™ R & O Fluids are ultimately biodegradable¹ vegetable based formulas that were designed specifically to replace mineral oil based turbine oils in environmentally sensitive hydroelectric (water) turbine bearings. These bearings are subject to humid/ moist conditions because of occasional seal leakage, but operate cooler than gas and steam turbine bearings. Bio-AW Turbine™ Fluids are formulated to perform in R & O systems that require anti-foam, anti-rust, anti-oxidation, and demulsibility properties. They are highly inhibited against moisture and rusting in both fresh and sea water and pass both A and B Sequences of the ASTM D-665 Turbine Oil Rust Test. Incorporating the super high viscosity index of the Stabilized* High Oleic Base Stocks (HOBS) into the formula, gives multi-grade synthetic base oil performance by boosting the viscosity index to synthetic levels. This super high viscosity index of the HOBS naturally improves the thermal shear stability of the formula and increases load capacity. The HOBS's extremely low volatility increases the flash and fire safety features in the formula. A zinc-free additive system has also been developed that is environmentally friendly and exceeds the load stage 10 in the FZG (DIN51354) requirements for both turbine oils and reduction gears. They also meet the requirements for an ashless GL-3 gear oil. Bio-AW Turbine™ R & O Fluids are ENVIRONMENTALLY RESPONSIBLE products that are formulated from renewable agricultural plant resources. We believe Earth's environmental future rests in the use of renewable materials.

Typical Specifications

ISO Grade	32	46	68	100
API Gravity @ 60°F.	30.4	30.0	28.1	27.3
Pounds/Gallon @ 60°F.	7.28	7.30	7.38	7.42
Specific Gravity @60°F.	.874	.876	.886	.891
VISCOSITIES:				
@100° C., cSt.	6.9	9.67	12.5	16.6
@40° C., cSt.	30.87	43.8	64.1	92.1
Viscosity Index	184	216	198	196
Flash Point, COC, °C	236	243	270	280
Pour Point, °C	-40	-39	-36	-30
Copper Corrosion Strip 3hr @ 100°C	1B	1B	1B	1B
4 Ball Wear, 1h, 167°F, 1200 RPM, 40kg	.40	.40	.40	.40
FZG Test	12	12	12	12
Demulsibility (ASTM D-1401)	40/40/0	40/40/0	40/40/0	40/40/0
Foam Sequence I, II, III (ASTM D-892)	0	0	0	0
Rust Prevention, (ASTM D-665 A&B)	Pass	Pass	Pass	Pass
Rotary Bomb Oxidation, (min)	360	360	360	360

STABILIZED by Renewable Lubricants* is RLI's trademark on their proprietary and patented anti-oxidant, anti-wear, and cold flow technology. High Oleic Base Stock (HOBS) are agricultural vegetable oils. This Stabilized technology allows the HOBS to perform as a high performance formula in high and low temperature applications, reducing oil thickening and deposits.

¹ Ultimate Biodegradation (Pw1) within 28 days in ASTM D-5864 Aerobic Aquatic Biodegradation of Lubricants

Patented Product: US Patent 6,383,992, US Patent 6,534,454 with additional Pending and Foreign Patents

* Trademark of Renewable Lubricants, Inc.

Copyright 1999 Renewable Lubricants, Inc.

Availability **F.O.B. :Bolton, ON, Canada** **5 Gallon Pails** **Drums** **Bulk**