



Renewable Lubricants, Inc.

Distributed By: DM's Bio-Based Fluid Supply Inc.
10 McEwan Dr. W, Unit 4B
Bolton, ON, Canada L7E 1H1
Voice: 905.951.1100 Fax: 905.951.2100
www.dmsbiobased.ca

Bio-Gearhead™ Oils



"Bio-based Lubricants that Perform Like Synthetics"

A Gearhead is the laymen's language for the right angle gear drive commonly used to reduce the speed of an irrigation engine to drive water well turbine pumps. These gear sets do not require Hypoid level of EP and because of this, the lubricant most commonly specified by makers of these gear reducers is an R & O or GL-3 type circulating oil in SAE 30 or higher viscosity. This formula has combined Stabilized technology with HOBS and mild EP/antiwear additives. The result is an ultimately biodegradable¹ product which has the long life heat stability but which additionally offers the protection advantages of the mild EP and antiwear of an API "GL-3" type gear lube. Bio-Gearhead™ Oils are ENVIRONMENTALLY RESPONSIBLE lubricants that are formulated from renewable agricultural plant resources. We believe Earth's environmental future rests in the use of renewable material.

Typical Specifications

<u>SAE Engine Grade</u>	<u>10W30</u>	<u>15W40</u>
API Gravity @ 60°F. (D-287)	30.0	27.3
Pounds/Gallon @ 60°F.	7.3	7.42
Specific Gravity @60°F. (D-287)	0.876	0.891
VISCOSITIES:		
@100°C., cSt. (D-445)	9.75	16.1
@40°C., cSt. (D-445)	43.17	91
Viscosity Index (D-2270)	216	190
Flash Point, COC, °C (D-92)	243	280
Pour Point, °C (D-97)	-36	-27
Copper Corrosion Strip 3hr @ 100°C (D-130)	1B	1B
4 Ball Wear, 1h, 167°F, 1200 RPM, 40kg (D-4172)	.40	.40
FZG Test (DIN 51517)	12	12
Demulsibility (D-1401)	40/40/0	40/40/0
Foam Sequence I, II, III (D-892)	0	0
Rust Prevention (D-665 A&B)	Pass	Pass

Features

- (1) API Service Classifications GL-1, GL-2, GL-3
- (2) Super high viscosity index and low pour point for wide temperature usage
- (3) Fortified with additives to resist wear, oxidation, rust and foam

STABILIZED by Renewable Lubricants* is RLI's trademark on their proprietary and patented anti-oxidant, anti-wear, and cold flow technology. High Oleic Base Stock (HOBS) are agricultural vegetable oils. This Stabilized technology allows the HOBS to perform as a high performance formula in high and low temperature applications, reducing oil thickening and deposits.

¹ Ultimate Biodegradation (Pw1) within 28 days in ASTM D-5864 Aerobic Aquatic Biodegradation of Lubricants

Patented Product: US Patent 6,383,992, US Patent 6,534,454 with additional Pending and Foreign Patents

* Trademark of Renewable Lubricants, Inc.

Copyright 1999 Renewable Lubricants, Inc.

Availability F.O.B. :Bolton, ON, Canada 5 Gallon Pails Drums Bulk