



Renewable Lubricants, Inc.

Distributed By: DM's Bio-Based Fluid Supply Inc.
10 McEwan Dr. W, Unit 4B
Bolton, ON, Canada L7E 1H1
Voice: 905.951.1100 Fax: 905.951.2100
www.dmsbiobased.ca



Bio-Metal Cool™ GP

General Purpose Water Emulsifiable Metal Working Fluid

"Bio-based Lubricants that Perform Like Synthetics"

Bio-Metal Cool™ GP is a general-purpose bio-based concentrate designed for use on both ferrous and nonferrous metals. This technologically advanced formula contains an environmentally friendly, additive system to allow performance in many metalworking applications. It provides excellent corrosion protection and is non-staining to aluminum and yellow metals. This (Biopreferredsm) vegetable based formulation is designed to offer good natural EP performance without the use of active sulfur and chlorinated EP additives making a more economical general-purpose type coolant (For heavier metal working applications that require additional EP, see Bio-Metal Cool™ HD). Performance is enhanced by use of the Stabilized* HOBS's, natural fatty acid composition, which provides cutting tool wetting and oiliness. The super high viscosity index of the Stabilized HOBS adds additional lubrication qualities to this high performance lubricant. The formulation is free of diethanolamine, secondary amines, secondary amide emulsifiers, nitrite corrosion inhibitors, phenolic biocides, and nonylphenol non-ionic surfactants. Solutions are white to off-white and stable in the hardest of waters. Bio-Metal Cool™ GP is formulated with a preservative to give long trouble-free service with a minimum of maintenance of its cleanliness.

Bio-Metal Cool™ GP is ENVIRONMENTALLY RESPONSIBLE cutting oil that is formulated from renewable agricultural plant resources. We believe Earth's environmental future rests in the use of renewable materials. EPA, OSHA, and worker acceptance is high with bio-based products (ISO 14000).

Application:

Bio-Metal Cool™ GP easily emulsifies in water with an ideal concentration range of 3% to 10%. At these levels, it is effective for grinding and machining of ferrous metals, ferrous alloys, stainless steel, aluminum, brass and bronze. At levels of 5% or greater, it is effective as a temporary rust inhibitor for ferrous metals. Bio-Metal Cool™ GP may be used as a quenching agent for nuts, bolts, screws and similar products. Alkaline cleaners or vapor degreasing can easily remove any residual film.

Typical Data:

9.0 pH @ 5% by volume in water
5% dilution in 200 ppm hardness water (IP 125) No corrosion (0/0-0 results)
Falex Pin & V block: 45 lb. in torque at 4000 psi
Four ball wear test: Avg. coefficient of friction 0.08
(5% dilution) Scar diameter in mm 0.51
Biodegradable in its neat form without preservative

This product is formulated with a preservative to prevent bacteria and fungus growth. Consult RLI's technical service for a neutral pH biocide if tank side application is required.

STABILIZED by Renewable Lubricants* is RLI's trademark on their proprietary and patented anti-oxidant, anti-wear, and cold flow technology. High Oleic Base Stock (HOBS) are agricultural vegetable oils. This Stabilized technology allows the HOBS to perform as a high performance formula in high and low temperature applications, reducing oil thickening and deposits.

Patented Product: US Patent 6,383,992, US Patent 6,534,454 with additional Pending and Foreign Patents

* Trademark of Renewable Lubricants, Inc.

Copyright 1999 Renewable Lubricants, Inc.

Availability **F.O.B. :Bolton, ON, Canada**

5 Gallon Pails

Drums

Bulk