



## Renewable Lubricants, Inc.

Distributed By: DM's Bio-Based Fluid Supply Inc.  
10 McEwan Dr. W, Unit 4B  
Bolton, ON, Canada L7E 1H1  
Voice: 905.951.1100 Fax: 905.951.2100  
[www.dmsbiobased.ca](http://www.dmsbiobased.ca)

# **MaxxLife™ HT 600 High Temperature Heavy Duty Grease**

## **NLGI # 2**

This High Temperature EP grease is a state-of-the-art product, characterized by exceptional mechanical and oxidation stability. MaxxLife HT™ 600 is the big brother to the little brother MaxxLife HT™ 220 (see MaxxLife HT 220 data sheet). MaxxLife HT™ 600 is formulated with a heavier base oil to improve performance in larger, heavier loaded, slower moving bearings, and sliding surfaces where the use of a grease with a much heavier base oil is beneficial or required. The extremely high load carrying ability, excellent resistance to water, superior corrosion protection, and outstanding stability in high temperatures, makes it a premium high performance heavy duty grease. It contains no heavy metals or other harmful or environmentally undesirable additives. This EP grease is formulated with a state-of-the-art synthetic non-soap thickener that gives long life at high temperatures, high extreme pressure characteristics and exceeds NLGI GC/LB (ASTM D-4950).

**Applications:** MaxxLife HT™ 600 simply adds a heavier cushioning film between metal to metal surfaces under heavier loads or in large equipment where close tolerances and high speeds are not a concern such as: industrial and mining machinery, transportation, agricultural, construction and forestry equipment, and marine applications. As a general rule, use MaxxLife HT™ 600 in bearings larger than 3 in. shaft diameter and/or operating less than 1,800 RPM. Large journal, roller, and ball bearings in paper mills, rubber mills, steel mills, bridge bearings, turn tables, conveyors, electric motors, pumps, wheel bearings, and also fifth wheels, hinge pins, king pins, and chassis are typical applications that can benefit from the use of MaxxLife HT™ 600.

- Unique high performance heavy duty industrial grease
- Increases bearing life 2-4 times over conventional (soap-based) grease lubricants (e.g. Lithium/Lithium Complex, etc.)
- Provides significant protection in automotive, industrial and agricultural wheel bearing applications where temperatures can be high due to heat from disc brakes
- Excellent for chassis lubrication because of superior low temperature properties, shear stability, and water resistant
- Preferred grease for lubrication of antifriction bearings
- Recommended for (Seal For Life) Applications
- Outstanding corrosion protection
- Environmentally friendly
- Excellent compatibility with other greases

### **Typical Specifications:**

Base Oil Viscosity SUS @ 100 °F	2600
Viscosity SUS @ 210 °F	156
Pour Point, °F	+5
V.I.	95
Dropping Point F (D-566) °F (°C)	+572 (+300)
Water washout (D-1264) @ 79°C (175°F) % loss	2.75
4-Ball wear test (D-2266) m./m scar, 40kg, 1200 RPM 75°C, 1 H	0.39
4-Ball EP test (D-2596)	
LWI, kg	65
Weld point, kg	500
Timken OK load (D-2509) lbs	65
Pen. @ 25°C (77°F) (D-217), mm/10	
Pen. worked 60 strokes	270
Pen. worked 100,000 strokes change from 60 strokes	+2
Roll Stability (D-1831) Pen.	+19
Oil Separation (D-1742) -24 hours @ 25°C (77°F)	0.17
Rust test rating (D-1743)	Pass
Oxidation Stability – (D-942)	
psi press. drop/100 hours	0
psi press. drop/500 hours	2
psi press. drop/1000 hours	9
Wheel bearing leakage grams (D-1263) modified @ 163°C (325°F)	0.4

Patented Product with Pending and Foreign Patents

\* Trademark of Renewable Lubricants, Inc.  
Copyright 1999 Renewable Lubricants, Inc.

**Availability    F.O.B. :Bolton, ON, Canada    16 oz. Tubes    35 lb Pails    120 lb Kegs    400 lb Drums**