



Renewable Lubricants, Inc.

Distributed By: DM's Bio-Based Fluid Supply Inc.
10 McEwan Dr. W, Unit 4B
Bolton, ON, Canada L7E 1H1
Voice: 905.951.1100 Fax: 905.951.2100
www.dmsbiobased.ca

Bio-Pro™ Bar & Chain Oils



"Bio-based Lubricants that Perform Like Synthetics"

Bio-Pro™ Oils are professional, ultimately biodegradable¹ bio-based bar and chain oils. Bio-Pro™ Oils combines agricultural vegetable oils with patented additive technology to provide **high performance**, biodegradable lubricants. A high level of tackiness with anti-wear and extreme pressure additives prevent oil fling off from chains and sprockets reducing wear. It has been recognized that the use of mineral lubricants poses certain environmental risks. Leakages, emissions and spillages, when handling lubricating oil, lead to direct pollution of the surroundings and the environment. Bio-Pro™ Oils were developed to ultimately biodegrade when lost into the environment.

Bio-Pro™ Oils are very tacky, tough, pitch dissolving lubricants that are recommended for chain saw bars and industrial chains and sprockets including those used in pulp and paper mills, saw mills, plywood mills, and general manufacturing. Other possible uses include chain drives on straddle lift lumber carriers, ATV and motorcycle chains, farm equipment, automatic and hand operated oilers.

Performance

Professionals love the Performance of Bio-Pro™ Bar & Chain Oils

A side-by-side comparison with conventional petroleum oil based bar & chain lubricants were performed. Testimonials have been reported from professional fire fighters cutting fire trails in New Mexico, that Bio-Pro™ SAE 15W50 has increased the bar and chain life 2 to 3 times over previous petroleum formulas. Bio-Pro™ reduces bar and chain maintenance and critical down time during fires.

Typical Specifications

	SAE 10W30	SAE 15W50
Specific Gravity @ 15.6 ⁰ C.	.88	.89
Viscosity @ 40 ⁰ C., cSt.	63	106
Viscosity @ 100 ⁰ C., cSt.	12	18.6
Viscosity Index	190	196
Flash Point, ⁰ C. COC	242	280
Pour Point, ⁰ C.	-39	-29
Brookfield Vis D-2983, cps @ -25 ⁰ C	4,000	12,000
4-Ball Wear (mm)	.40	.40

STABILIZED by Renewable Lubricants* is RLI's trademark on their proprietary and patented anti-oxidant, anti-wear, and cold flow technology. High Oleic Base Stock (HOBS) are agricultural vegetable oils. This Stabilized technology allows the HOBS to perform as a high performance formula in high and low temperature applications, reducing oil thickening and deposits.

¹ Ultimate Biodegradation (Pw1) within 28 days in ASTM D-5864 Aerobic Aquatic Biodegradation of Lubricants

Patented Product: US Patent 6,383,992, US Patent 6,534,454 with additional Pending and Foreign Patents

* Trademark of Renewable Lubricants, Inc.
Copyright 1999 Renewable Lubricants, Inc.

Availability **F.O.B. :Bolton, ON, Canada** **5 Gallon Pails** **Drums** **Bulk**